


## Product Information CC750



**BOSCH**

Invented for life



CC750

### Customer benefits:

- ▶ Excellent system know-how
- ▶ Smart concepts for system safety
- ▶ Secured supply
- ▶ Long- term availability of manufacturing processes and products
- ▶ QS9000 and ISO/TS16949 certified

### Features

- ▶ Supports CAN Protocol Version 2.0 Part A, B
- ▶ Programmable Bit Rate
- ▶ 15 Message Objects of 8-Byte Data Length (14 Tx/Rx Buffers / 1 Rx Buffer)
- ▶ Programmable Global Mask (Standard and Extended Message Identifier)
- ▶ Serial Interface
- ▶ SOIC16-W Package

The CC750 serial communications controller is a highly integrated device that performs serial communication according to the CAN protocol. It performs all serial communication functions such as transmission and reception of messages, message filtering, transmit search, and interrupt search with minimal interaction from the host microcontroller, or CPU.

The CC750 supports the standard and extended message frames in CAN Specification

2.0 Part A and Part B. It has the capability to transmit, receive, and perform message filtering on extended message frames.


The CC750 features a serial interface (SPI) to connect a CPU without spending many interconnections.

The CC750 provides storage for 15 message objects of 8-byte data length. Each message object can be configured as either transmit or receive except for the last message object. The last message object is a receive-only buffer with a special mask design to allow select groups of different message identifiers to be received.

The CC750 also implements a global masking feature for message filtering. This feature allows the user to globally mask any identifier bits of the incoming message. The programmable global mask can be used for both standard and extended messages.


The CC750 is available in a SOIC16-W package. It is designed for the automotive temperature range (-40 C to +125 C).

## Block Diagram



## PIN configuration

Package: SOIC16-W



### CAN-Protocol Controller

The CAN controller controls the data stream between the Memory (parallel data) and the CAN bus line (serial data). The CAN controller also handles the error management logic and the message objects.

### Message Memory

Stores Message Objects and Identifier Masks and contains Rx/Tx Shift Register.

### Interface Logic

The CPU Interface Logic controls the data stream between the SPI (serial data) and the Memory (parallel data).

## Contact

**Robert Bosch GmbH**  
Sales Semiconductors  
Postbox 13 42  
72703 Reutlingen  
Germany  
Tel.: +49 7121 35-2979  
Fax: +49 7121 35-2170

**Robert Bosch Corporation**  
Component Sales  
38000 Hills Tech Drive  
Farmington Hills, MI 48331  
USA  
Tel.: +1 248 876-7441  
Fax: +1 248 848-2818

**Robert Bosch K.K.**  
Component Sales  
9-1, Ushikubo 3-chome  
Tsuzuki-ku, Yokohama 224  
Japan  
Tel.: +81 45 9 12-83 01  
Fax: +81 45 9 12-95 73

E-Mail: [bosch.semiconductors@de.bosch.com](mailto:bosch.semiconductors@de.bosch.com)

Internet: [www.bosch-semiconductors.de](http://www.bosch-semiconductors.de)

© 02/2006 All rights reserved by Robert Bosch GmbH including the right to file industrial property rights  
Robert Bosch GmbH retains the sole powers of distribution, such as reproduction, copying and distribution.

For any use of products outside the released application, specified environments or installation conditions no warranty shall apply and Bosch shall not be liable for such products or any damage caused by such products.