

DESCO



09108 - WRISTBAND, JEWEL, ADJ ELASTIC EMERALD, 4MM

- **High visibility**
Bright colors allow supervisor to see that worker is wearing wrist strap
- **Solid stainless steel wrist band stud machined to exacting tolerances and precise profile**
Ensures reliable path-to-ground connection to spring loaded 4mm stainless steel constant contact coil cord snap.
Lifetime warranty on our wrist band stud
- **Durable, lightweight fabric**
Some users prefer the softness, comfort and flexibility of this material
- **Has silver impregnated nylon knitted on inside for superior conductivity**
Reliably removes generated static charges
- **Made with pure silver irreversibly bound to fibers providing both antimicrobial and anti-odor performance**
- **Adjustable**
Only one item to stock; may be fitted to almost all people
- **Locking clasp**
Band locked so it will not slip
- **Unique patented** adjustment design eliminates exposed conductive “tail” of band**
Provides added safety eliminating chance of providing inappropriate ground path
- **Medical grade 300 series stainless steel used for all metal parts**
Eliminates allergic skin reaction for most people
- **Non-shedding, non-sloughing band material**
Safe for microelectronics
- **Date coded**
Providing lot tractability to ensure quality control
- **Made in America**

* US Patent 5,951,337, **US Patent 4,662,695

Circumference - 2.5" - 14"

NOTE: All bands have a 4mm snap stud. Complete wrist strap kits include an alligator clip. Wrist strap kits include an alligator clip for occasions when a grounded banana jack is not available. However, best industry practice is that ESD Ground Connections should be firm fitting connecting devices such as metallic crimps, snaps and banana plugs to be connected to designated ground points. Use of alligator clips is not recommended. (Ref: JEDEC Standard No. 625-A)

Jewel™ Wrist Bands meet and exceed the Wrist Band and Wrist Cord requirements of ANSI/ESD S20.20.