

## Extending the BL54 Family with Flexible Drop-In Options

Experience a new pinnacle of flexibility, performance, efficiency, and security with our new BL54L10 series, built on Nordic Semiconductor's powerful **nRF54** silicon. Elevating what you know and love from the nRF52 series, this next generation redefines Bluetooth LE and 802.15.4 solutions. The BL54L10 enables flexibility in design choice and future proofing with drop in memory and RAM module options with its sister part, the BL54L15.

Powered by **Nordic's nRF54L10** SoC, our compact BL54L10 modules deliver secure and robust Bluetooth LE and 802.15.4 with flexible programming via the Nordic SDK, Zephyr RTOS and **Canvas Software Suite**.

Featuring a **128MHz ARM Cortex M33** and **128MHz RISC-V coprocessor**, supported by 1.0 MB non-volatile memory and 192 KB RAM, the BL54L10 modules offer a reduced flash and RAM option versus the BL54L15, all in the same footprint. The BL54L10 series brings out all nRF54L10 hardware features and capabilities including up to **+8 dBm** transmit power, **1.7V – 3.6V** supply considerations, and **NFC A-Tag** implementation.

It's further enhanced with state-of-the-art security and is designed for PSA Certified level 3. It supports services such as Secure Boot, Secure Firmware Update, Secure Storage plus protection from physical attacks.



- **Nordic nRF54L10** – 6x6 QFN48 with 31 GPIOs utilized.
- **Multi-protocol support:** Bluetooth 5.4 LE, 802.15.4 (Thread/Matter)
- **Cortex M33** processor core: 128 MHz ARM Cortex M33
- **RISC-V** co-processor core: 128 MHz VPR
- **Memory:** 1.0MB non-volatile memory, 192 KB RAM
- **High Speed Peripherals:** - HS-SPI/UART, software defined peripherals on 128 MHz VPR, GPIO – 1x 64 MHz Port, 1.7 – 2.6V, 11 GPIOs
- **Low Leakage Peripherals:** 2x QDEC, 7x Timer, Global RTC, 2x WDT, NFC A-Tag, TEMP, I2S, COMP, 3x PWM, LPCOMP, 14-bit 8CH ADC, 5x TWI/SPI/UART, GPIO (2x 8 MHz Port (P0, P1), 19 GPIO's, 1.7-2.6V, 31 GPIO)
- **Antenna choice** – integrated pre-certified **PCB Trace antenna** or external antenna support via **MHF4 connector**
- **Ultra-small footprint** (14 mm x 10 mm x 1.6 mm)
- **Extended Industrial Temperature Rating** (-40° to +105 °C)
- **Development choice:** Zephyr RTOS, Nordic nRF Connect SDK & Canvas
- **Bluetooth LE:** Peripheral/Central, 2 Mbps (high throughput), LE Coded (long range), AoA/AoD, Mesh
- **Firmware Over the Air (FOTA)** via MCUboot and Zephyr
- **Hostless operation** – Multi Core MCU reduces BOM
- **Fully featured development kits** to jump start Bluetooth LE development
- **100% pin for pin** and mechanically the same form factor as **BL54L15 series**
- Mechanically same form factor as **BL652 Series**

## Key Features



### Best in Class Multiprotocol Radio

Best-in-class multiprotocol radio with up to 8 dBm TX power (with 1 dB steps) and -98 dBm RX sensitivity for 1 Mbps BLE. Supports BT 5.4 features and upcoming BT specifications, as well as Bluetooth mesh, Thread, and Matter.



### Advanced Security

Designed for PSA Certified Level 3 with Secure Boot, Secure Firmware Update, and Secure Storage. Integrated tamper sensors detect attacks and take action, and cryptographic accelerators are hardened against side-channel attacks.



### True Industrial Operating Range

Designed and certified to the highest industrial temperature range of -40 °C to +105 °C for every component utilized.



### Global Approvals – Make Yourself at Home

Carries several modular FCC, ISED, EU, RCM, MIC, KC for Bluetooth & 802.15.4



### Personal Support from Design to Manufacture

Our industry-renowned support is passionate about helping you speed your design to market.

## Application Areas



**Building Automation**



**Security**



**Medical Peripherals**



**Industrial Sensors**

## Specifications

Category	Feature	Specification
Wireless Specification	Bluetooth®	v5.4
	802.15.4	Thread and Matter
	NFC	A-Tag
	Frequency	2.402 - 2.480 GHz
	Transmit Power	+ 8 dBm (maximum). Configurable down to -8 dBm
	Receive Sensitivity	-98 dBm (typical BLE 1 Mbps) -106 dBm (typical BLE 125 kbps)
	Link Budget	106 dB (@ Bluetooth LE 1 Mbps), 114 dB (@ Bluetooth LE 125 kbps)
	Antenna Options	PCB trace antenna or MHF4 connector for external antennas
	Raw Data Rates (Air)	BLE: 1 Mbps, 2 Mbps, 125 kbps, 500 kbps 802.15.4-2006: 250 kbps
Host Interface and Peripherals	UART Interface	TX, RX, CTS, RTS, DTR, DSR, DCD, RI (GPIO) Default: 115200, N, 8, 1. Configurable from 1200 bps to 1 Mbps
	Other	31 multifunction GPIO's that can provide: <ul style="list-style-type: none"> <li>• 5x UART/SPI/TWI</li> <li>• 8x ADC channels (1 pin each)</li> <li>• 2x I2S (5 GPIO pins)</li> <li>• 3x PWM output (1 GPIO pin per PWM)</li> <li>• 7x TIMER (no GPIO needed unless required)</li> <li>• 2 GPIO pins for 32.768 kHz crystal</li> <li>• 1x NFC (2 GPIO pins)</li> <li>• 2x QDEC</li> <li>• 20x Wakeup pins</li> </ul>
Key Bluetooth LE Features	Bluetooth Low Energy	<ul style="list-style-type: none"> <li>• GATT client &amp; GATT server - Any adopted/custom services</li> <li>• Central/Peripheral roles</li> <li>• Bluetooth LE Mesh</li> <li>• CODED PHY</li> <li>• 2M PHY</li> <li>• LE advertising extensions</li> <li>• LE secure connections</li> <li>• Data packet length extensions</li> <li>• LE privacy v1.2</li> <li>• LE ping</li> <li>• DTM Firmware (Test Modes)</li> </ul>
Programmability Options	Nordic SDK	Software/Support available from Nordic directly <a href="https://devzone.nordicsemi.com/">https://devzone.nordicsemi.com/</a>
	Zephyr RTOS	Software/Support available from <a href="https://www.zephyrproject.org/">https://www.zephyrproject.org/</a>
	Canvas SW Suite	Software/ Support available from <a href="https://www.ezurio.com/canvas/software-suite">https://www.ezurio.com/canvas/software-suite</a>
FW upgrade		Via UART or JTAG
Supply Voltage		Normal Voltage Mode: 1.7V - 2.7V Medium Voltage Mode: 1.8V - 3.6V
Power Consumption	Current	Max Peak Radio Current (@ +8 dBm TX) - TBC mA (DCDC at 3V)
		Max Peak Radio Current (@ 0 dBm TX) - TBC mA (DCDC at 3V)
		Standby Doze - TBC µA
Physical	Dimensions	14 mm x 10 mm x 1.6 mm
Environmental	Temp Range	-40°C to +105°C
Miscellaneous	Lead Free	Lead-free and RoHS-compliant
	Development Kit	Development board and free software tools
Development Tools	Utilities	Nordic nRFConnect - Android and iOS applications
		UART firmware upgrade Xbit Tools and utilities
Qualifications	Bluetooth®	Complete Declaration ID
Regulatory	Approvals	FCC, ISCED, EU, UKCA, RCM, MIC, KC - All BL54L10 Series are Bluetooth & 802.15.4 certified (all pending)

For full specifications on BL54L10 modules, please see the appropriate datasheet.

## Ordering Information

Part	Description
453-00225R	Module, BL54L10, (Nordic nRF54L10), Trace antenna, Tape/Reel
453-00226R	Module, BL54L10, (Nordic nRF54L10), MHF4 Connector, Tape/Reel
453-00225C	Module, BL54L10, (Nordic nRF54L10), Trace antenna, Cut Tape
453-00226C	Module, BL54L10, (Nordic nRF54L10), MHF4 Connector, Cut Tape
453-00225-K1	Development kit, Module, BL54L10 (Nordic nRF54L10), Trace antenna
453-00226-K1	Development kit, Module, BL54L10 (Nordic nRF54L10), MHF4 Connector

Ezurio's products are subject to standard [Terms & Conditions](#).