

PRODUCT DATASHEET Cute series

last update 18/3/2013



Family Type LED Color Diame Height





Ordering number	C10754_CUTE-3-SS		
Family	Cute	FWHM	19 degrees
Туре	-	Efficiency	91 %
LED	XM-L	cd/lm	5.280
Color	Clear	Gerber File	Available
Diameter	35 mm		
Height	15 mm	Pin height 3mm	
Style	Round	Fin neight Smin	
Optic Material	PMMA		
Holder Material	- Dia alua		
Fastening Status	Pin, glue Ready		
Status	Reauy		
Ordering number	C11333_CUTE-3-SS		
Family	Cute	FWHM	19 degrees
Туре	-	Efficiency	91 %
LED	XM-L	cd/lm	-
Color	Clear	Gerber File	Available
Diameter	35 mm		
Height	15 mm		
Style	Round		
Optic Material	PMMA		
Holder Material	- Dia alua		
Fastening Status	Pin, glue		
	Ready		
Ordering number	C10755_CUTE-3-M		
	C10755_CUTE-3-M	FWHM	25 degrees
Ordering number Family Type		FWHM Efficiency	25 degrees 90 %
Family	Cute		-
Family Type	Cute -	Efficiency	90 %
Family Type LED	Cute - XM-L	Efficiency cd/lm	90 % 3.510
Family Type LED Color Diameter Height	Cute - XM-L Clear	Efficiency cd/lm Gerber File	90 % 3.510 Available
Family Type LED Color Diameter Height Style	Cute - XM-L Clear 35 mm 15 mm Round	Efficiency cd/lm	90 % 3.510 Available
Family Type LED Color Diameter Height Style Optic Material	Cute - XM-L Clear 35 mm 15 mm Round PMMA	Efficiency cd/lm Gerber File	90 % 3.510 Available
Family Type LED Color Diameter Height Style Optic Material Holder Material	Cute - XM-L Clear 35 mm 15 mm Round PMMA	Efficiency cd/lm Gerber File	90 % 3.510 Available
Family Type LED Color Diameter Height Style Optic Material Holder Material Fastening	Cute - XM-L Clear 35 mm 15 mm Round PMMA - Pin, glue	Efficiency cd/lm Gerber File	90 % 3.510 Available
Family Type LED Color Diameter Height Style Optic Material Holder Material Fastening Status	Cute - XM-L Clear 35 mm 15 mm Round PMMA - Pin, glue Ready	Efficiency cd/lm Gerber File	90 % 3.510 Available
Family Type LED Color Diameter Height Style Optic Material Holder Material Fastening Status	Cute - XM-L Clear 35 mm 15 mm Round PMMA - Pin, glue	Efficiency cd/lm Gerber File	90 % 3.510 Available
Family Type LED Color Diameter Height Style Optic Material Holder Material Fastening Status	Cute - XM-L Clear 35 mm 15 mm Round PMMA - Pin, glue Ready	Efficiency cd/lm Gerber File	90 % 3.510 Available
Family Type LED Color Diameter Height Style Optic Material Holder Material Fastening Status Ordering number	Cute - XM-L Clear 35 mm 15 mm Round PMMA - Pin, glue Ready C11334_CUTE-3-M	Efficiency cd/lm Gerber File Location Pin total h	90 % 3.510 Available neight 3mm.
Family Type LED Color Diameter Height Style Optic Material Holder Material Fastening Status Ordering number Family	Cute - XM-L Clear 35 mm 15 mm Round PMMA - Pin, glue Ready C11334_CUTE-3-M Cute	Efficiency cd/lm Gerber File Location Pin total h	90 % 3.510 Available neight 3mm. 25 degrees
Family Type LED Color Diameter Height Style Optic Material Holder Material Fastening Status Ordering number Family Type	Cute - XM-L Clear 35 mm 15 mm Round PMMA - Pin, glue Ready C11334_CUTE-3-M Cute	Efficiency cd/lm Gerber File Location Pin total h FWHM Efficiency	90 % 3.510 Available neight 3mm. 25 degrees
Family Type LED Color Diameter Height Style Optic Material Holder Material Fastening Status Ordering number Family Type LED	Cute - XM-L Clear 35 mm 15 mm Round PMMA - Pin, glue Ready C11334_CUTE-3-M Cute - XM-L	Efficiency cd/lm Gerber File Location Pin total h FWHM Efficiency cd/lm	90 % 3.510 Available neight 3mm. 25 degrees 90 %
Family Type LED Color Diameter Height Style Optic Material Holder Material Fastening Status Ordering number Family Type LED Color Diameter Height	Cute - XM-L Clear 35 mm 15 mm Round PMMA - Pin, glue Ready C11334_CUTE-3-M Cute - XM-L Clear	Efficiency cd/lm Gerber File Location Pin total h FWHM Efficiency cd/lm	90 % 3.510 Available neight 3mm. 25 degrees 90 %
Family Type LED Color Diameter Height Style Optic Material Holder Material Fastening Status Ordering number Family Type LED Color Diameter Height Style	Cute - XM-L Clear 35 mm 15 mm Round PMMA - Pin, glue Ready C11334_CUTE-3-M Cute - XM-L Clear 35 mm 15 mm Round	Efficiency cd/lm Gerber File Location Pin total h FWHM Efficiency cd/lm	90 % 3.510 Available neight 3mm. 25 degrees 90 %
Family Type LED Color Diameter Height Style Optic Material Holder Material Fastening Status Ordering number Family Type LED Color Diameter Height Style Optic Material	Cute - XM-L Clear 35 mm 15 mm Round PMMA - Pin, glue Ready C11334_CUTE-3-M Cute - XM-L Clear 35 mm 15 mm Round PMMA	Efficiency cd/lm Gerber File Location Pin total h FWHM Efficiency cd/lm	90 % 3.510 Available neight 3mm. 25 degrees 90 %
Family Type LED Color Diameter Height Style Optic Material Holder Material Fastening Status Ordering number Family Type LED Color Diameter Height Style Optic Material Holder Material	Cute - XM-L Clear 35 mm 15 mm Round PMMA - Pin, glue Ready C11334_CUTE-3-M Cute - XM-L Clear 35 mm 15 mm Round PMMA -	Efficiency cd/lm Gerber File Location Pin total h FWHM Efficiency cd/lm	90 % 3.510 Available neight 3mm. 25 degrees 90 %
Family Type LED Color Diameter Height Style Optic Material Holder Material Fastening Status Ordering number Family Type LED Color Diameter Height Style Optic Material	Cute - XM-L Clear 35 mm 15 mm Round PMMA - Pin, glue Ready C11334_CUTE-3-M Cute - XM-L Clear 35 mm 15 mm Round PMMA	Efficiency cd/lm Gerber File Location Pin total h FWHM Efficiency cd/lm	90 % 3.510 Available neight 3mm. 25 degrees 90 %

May 8th 2013 18:23 Copyright Ledil Oy - Subject to change without prior notice - Page 1/3

Ledil Oy Salorankatu 10 24240 SALO Finland http://www.ledil.com email: ledil@ledil.com FAX: +358-2-733 8001



PRODUCT DATASHEET Cute series last update 18/3/2013

CREE (



Family	Cute
Туре	-
LED	XM-L
Color	Clear
Diameter	35 mm
Height	15 mm
Style	Round
Optic Material	PMMA
Holder Material	-
Fastening	Pin, glue
Status	Ready

Ordering number C10756_CUTE-3-W

FWHM Efficiency cd/Im Gerber File 42 degrees 83 % -Available

Location pin height 1.5mm

NOTE: The typical divergence will be changed by different color, chip size and chip position tolerance. The typical total divergence is the full angle measured where the luminous intensity is half of the peak value.

Ledil Oy Salorankatu 10 24240 SALO Finland



PRODUCT DATASHEET Cute series last update 18/3/2013



GENERAL INFORMATION

- Product series especially designed & optimized for XM-L series of LEDs.

- Special care taken to make light distribution as uniform as possible.

- Lens material optical grade PMMA with high UV and temperature resistance (105 degrees of Celcius / 220 degrees of Fahrenheit). Allows use of high current and temperature conditions.

Please find more information about used material from below:

http://ledil.fi/sites/default/files/Documents/Technical/Material/PMMA%208N%20UL94_Yellow%20Card.pdf http://ledil.fi/sites/default/files/Documents/Technical/Material/PMMA%208N%20PLEXIGLAS-Datasheet.pdf

- Fastening to PCB with appropriate adhesive. By clicking link below you can find Ledil recommended glue options.

http://www.ledil.com/datasheets/DataSheet_GLUES.pdf

NOTE 1: We advise customer to ensure the suitability and sufficiency of the bond in the end product. For example, mechanical stress, vibration and holes on the surface of the circuit boar weaken the strength of the glue.

NOTE 2: All surfaces where glue is applied must be clean, dry and free from grease and dirt. If cleaning of PCB surfaces is needed, please follow strictly the cleaning instructions of your LED manufacturer -this is important as cleaning shall under no circumstances damage LEDs or other electronics components on the PCB.

Further note that optical components shall not be cleaned with any chemicals - only micro fiber cloth may be used to remove fingerprints or other traces from handling.

Relative intensity of C10756_Cute-3-W-XM



