





ELECTRICAL SPECIFICATIONS		
Model Name	001-0012	
Operating Frequency (MHz)	2400-2500	4910-5850
VSWR	≤ 2.5:1	
Gain (dBi)	2.0	2.0
Nominal Impedance (Ohms)	50	
Polarization	Linear vertical	


MECHANICAL SPECIFICATIONS	
Dimensions – mm (inches)	114 x 13 (4.49 x 0.51)
Weight - g (oz.)	18.0 (0.63)
Radome Material	Black

ENVIRONMENTAL SPECIFICATIONS		
Operating Temperature – °C (°F)	-40 to +85°C (-40 to +185°F)	
UL Rating	UL 94HB	
Ingress Protection Rating	IP67	

CONFIGURATION

PART NUMBER	DESCRIPTION
001-0012	2.4/5.5 GHz waterproof dipole antenna for Reverse Polarity SMA connector
080-0013	U.FL to Reverse Polarity SMA cable, 105 mm, O-ring seal
080-0014	U.FL to Reverse Polarity SMA cable, 210 mm, O-ring seal

MECHANICAL DRAWING



TYPICAL ANTENNA REFLECTION PERFORMANCE

Straight Antenna Position



Bent Antenna Position






RADIATION PATTERNS


2.4 GHz (E-Plane)

Total Gain (RSS of Vertical and Horizontal Polarization) (dB)




5 GHz (E-Plane)

Total Gain (RSS of Vertical and Horizontal Polarization) (dB)




2.4 GHz (H-Plane)

Total Gain (RSS of Vertical and Horizontal Polarization) (dB)



5 GHz (H-Plane)

Total Gain (RSS of Vertical and Horizontal Polarization) (dB)



✓RoHS

Laird Connectivity warrants to the original end user customer of its products that its products are free from defects in material and workmanship. Subject to conditions and limitations Laird Connectivity will, at its option, either repair or replace any part of its products that prove defective because of improper workmanship or materials. This limited warranty is in force for the useful lifetime of the original end product into which the Laird Connectivity product is installed. Useful lifetime of the original end product may vary but is not to exceed five (5) years from the original date of the end product purchase.



Any information furnished by Laird Connectivity and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird Connectivity materials rests with the end user, since Laird Connectivity and its agents cannot be aware of all potential uses. Laird Connectivity makes no warranties as to the fitness, merchantability or suitability of any Laird Connectivity materials or products for any specific or general uses. Laird Connectivity materials or consequential damages of any kind. All Laird Connectivity products are sold pursuant to the Laird Connectivity Terms and Conditions of sale in effect from time to time, a copy of which will be furnished upon

support@lairdconnect.com

sales@lairdconnect.com

www.lairdconnect.com

© Copyright 2020 Laird Connectivity All Rights Reserved. Laird Connectivity, the Laird Connectivity logo, and other marks are trademarks or registered trademarks of Laird Connectivity or an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird Connectivity or any third party intellectual property rights.