


[myMicrochip Login](#) | [English](#) | [Chinese](#) | [Japanese](#)

search



- [Home](#)
- [Products](#)
- [Design](#)
- [Support](#)
- [Applications](#)
- [Buy/Sample](#)
- [Corporate](#)
- [What's New](#)

Search:

TDGL003

GO »

Refine Your Search

- All Microchip Content
- **Product Search**
- Development Tools
- Product Documents
 - Datasheets
 - Errata
 - Application Notes
 - Migration Guides
 - Brochures
 - User Guides
 - Programming Specifications
 - Videos
- Training and Webinars
- Knowledge Base and Support
- Discussion Forum/Wiki/Blog
- Product Change Notification
- Corporate Information
 - Sales
 - Finance
 - News and Events
 - Careers

Product Search - [Buy Online](#) | [Sample Online](#)Results 1 - 1 of 1 for **TDGL003**

Results per page: 10



TDGL003 - chipKIT Max32 Development Board. chipKIT™ Max32 by Digilent is an easy-to-use platform for developing advanced applications. chipKIT uses a modified version of the original Arduino™ IDE for compatibility with existing code examples, tutorials and resources. Pin-compatible with many Arduino shields that can operate at 3.3V.

- PIC32MX795F512L processor
- 512K Flash, 128K RAM
- Up to 80MHz operating speed
- USB 2.0 OTG controller
- 10/100 Ethernet MAC
- Dual CAN controllers
- 83 available I/O lines
- USB or externally powered
- USB cable required for programming (not included)

This low-priced item is not eligible for academic discount.

Digilent is a trusted 3rd Party Tool provider [Buy](#)