



[Products](#)
 [Applications](#)
 [Development Tools](#)
 [FAQ/Support](#)
 [Buy/Samples](#)
 [Technology](#)

[Products](#) >
 [MPU & MCU](#) >
 [Product Lineup](#) >
 78K0S, 78K0 General Purpose - All products with internal flash memory type (All Flash®) >
 78K0/KC2-L >

UPD78F0588GB-GAF-AX

[Specification](#)
 [Documentation](#)
 [Development Tools](#)

Go to Buy page

[Buy Now](#)

Specification

Core	
CPU	78K0 (8-bit)
Main oscillator	10 MHz external, 8 MHz internal
Clock supervising	—
Internal clock frequency (max.)	10 MHz
Instruction cycle time (min.)	100 ns
Interrupt channels	10 external, 16 internal

Memory	
Program memory	32 KB flash
RAM size	1 KB
Non-volatile memory size (EEPROM or emulation)	0 byte
ROM correction points	—

Interfaces	
Total number of I/Os	38
Open drain outputs	—
CAN	—
UART (asynchronous serial interface)	1 ch.
LIN	—
CSI (clocked serial interface)	1 ch.
I ² C	1 ch.
I ² S	—
On-chip debug interface	✓

Peripherals	
LCD controller/driver	—
A/D converter (10-bit)	11 ch.
Hardware multiplier	n/a
Hardware divider	n/a
DMA	—
Low Voltage Indicator	✓
Power-On Clear	✓
Other Peripherals	Operational Amplifier 2 channels

Timers	
Timers (8-bit)	4 ch.
Timers (16-bit)	1 ch.
Interval timers	—
Special timers	—
Watchdog timers	1 ch.
PWM (8-bit resolution)	4 ch.