

**Force Guided Relay SR6 A/B/C/V**

- 6 pole relay with force guided contacts according to EN 50205
- Reinforced insulation between all contacts

Typical applications  
Emergency shut-off, press control, machine control, elevator and escalator control, safety relays



F0206-EA





**Approvals**

VDE 128935, cULus E214024, TUV 968/EL 350, CQC 0617015576/77  
Technical data of approved types on request

**Contact Data**

Contact arrangement	3 form A + 3 form B contacts 3 NO + 3 NC, 4 form A + 2 form B contacts 4 NO + 2 NC, 5 form A + 1 form B contacts 5 NO + 1 NC
Rated voltage	250VAC
Max. switching voltage	400VAC
Rated current	8A
Contact material	AgSnO <sub>2</sub> , AgSnO <sub>2</sub> + 0.2µm Au
Contact style	single contact, force guided type A according to EN 50205
Min. recommended contact load	5V, 10mA
Initial contact resistance	≤100mΩ at 1A, 24VDC ≤20Ω at 10mA, 5VDC
Frequency of operation, with/without load	6/150min <sup>-1</sup>
Contact ratings, IEC60947-5-1, on 2 form A (NO) contact	AC15-5A DC13-6A
Mechanical endurance	10x10 <sup>6</sup> operations





**Coil Data**

Coil voltage range	5 to 110VDC
Max. coil power	1200mW or 800mW

**Coil versions, DC-coil 800mW**

Coil code	Rated voltage VDC	Operate voltage VDC	Release voltage VDC	Coil resistance Ω±10%	Rated power mW
K12	12	9	0.9	180	800
K15	15	11.3	1.5	281	801
K18	18	13.5	1.8	405	800
K21	21	16	2.1	551	800
K24	24	18	2.4	720	800
K36	36	27	3.6	1620	800

All figures are given for coil without pre-energization, at ambient temperature +23°C.



**Coil versions, DC-coil 1200mW**

Coil code	Rated voltage VDC	Operate voltage VDC	Release voltage VDC	Coil resistance Ω±10% <sup>1)</sup>	Rated coil power mW
005	5	3.8	0.5	21	1190
006	6	4.5	0.6	30	1200
009	9	6.8	0.9	68	1191
012	12	9	1.2	120	1200
018	18	13.5	1.8	270	1200
021	21	16	2.1	368	1198
024	24	18	2.4	480	1200
036	36	27	3.6	1080	1200
040	40	30	4.0	1333	1200
048	48	36	4.8	1920	1200
060	60	45	6	3000 <sup>1)</sup>	1200
110	110	83	11	10080 <sup>1)</sup>	1200

1) Coil resistance ±12%.

All figures are given for coil without pre-energization, at ambient temperature +23°C.

**Force Guided Relay SR6 A/B/C/V** (Continued)

**Insulation Data**

Initial dielectric strength	
between open contacts	1500V <sub>rms</sub>
between contact and coil	4000V <sub>rms</sub>
between adjacent contacts	3000V <sub>rms</sub>
Clearance/creepage	
between open contacts	microdisconnection
between contact and coil	≥5.5/5.5mm
between adjacent contacts	≥5.5/5.5mm
Insulation to EN 50178, type of insulation	
between contact and coil	reinforced
between adjacent contacts	reinforced

**Other Data**

Material compliance: EU RoHS/ELV, China RoHS, REACH, Halogen content refer to the Product Compliance Support Center at <a href="http://www.tycoelectronics.com/customer-support/rohssupportcenter">www.tycoelectronics.com/customer-support/rohssupportcenter</a>	
Ambient temperature	-25 to 70°C
Category of environmental Protection	RTIII
IEC 61 810	
Weight	30g
Resistance to soldering heat THT	260°C/5s
IEC 60068-2-20	
Packaging/unit	tube/10 pcs.

For more detailed information see product specification 2158003


**Accessories**

27E1079	SR6A and SR6B socket (1423991-1)
27E1081	SR6C socket (1423992-1)
24A243	Relay hold down clip (1423994-1)

For details see datasheet 1654787


**Dimensions**

SR6 A/B/C



S0367-DN

SR6 V




S0367-DU

**PCB layout / terminal assignment**


Bottom view

3 form A + 3 form B, 3 NO + 3 NC versions  
SR6 A




S0368-CA

4 form A + 2 form B, 4 NO + 2 NC versions  
SR6 B




S0368-CA


5 form A + 1 form B, 5 NO + 1 NC versions  
SR6 C




S0368-CE



S0368-CC




S0368-CB




S0368-CD

4 form A + 2 form B, 4 NO + 2 NC versions  
SR6 V

The design of the SR6 V allows clearance/creepage of 5.5 mm on the PCB.



S0368-CU



S0368-CV

**Force Guided Relay SR6 A/B/C/V** (Continued)

**Product code structure**

Typical product code **SR6 A 4 012**

<b>Type</b>	<b>SR6</b> Relay with force guided contacts SR6
<b>Contact arrangement</b>	<p><b>A</b> 3 form A + 3 form B contacts (3 NO + 3 NC)</p> <p><b>B</b> 4 form A + 2 form B contacts (4 NO + 2 NC)</p> <p><b>V</b> 4 form A + 2 form B contacts (4 NO + 2 NC)</p> <p><b>C</b> 5 form A + 1 form B contacts (5 NO + 1 NC)</p>
<b>Contact material</b>	<p><b>4</b> AgSnO<sub>2</sub> for 1200mW version</p> <p><b>6</b> AgSnO<sub>2</sub> + 0.2µm Au for 800mW version</p>
<b>Coil</b>	Coil code: please refer to coil versions table (e.g. 024=24VDC)

Available types please see Part number table

Product code	Type	Arrangement	Cont. material	Coil	Coil power	Alt. description	Part number			
SR6A4005	6 pole relay with force guided contacts	3 form A + 3 form B, 3 NO + 3 NC contactts	AgSnO <sub>2</sub>	5VDC	1200mW	V23050-A1005-A533	8-1415017-1			
SR6A4012				12VDC		V23050-A1012-A533	1-1415015-1			
SR6A4021				21VDC		V23050-A1021-A533	3-1415018-1			
SR6A4024				24VDC		V23050-A1024-A533	1415015-1			
SR6A4048				48VDC		V23050-A1048-A533	6-1415018-1			
SR6A4060				60VDC		V23050-A1060-A533	7-1415018-1			
SR6A4110				110VDC		V23050-A1110-A533	9-1415018-1			
SR6A6K12				AgSnO <sub>2</sub> +Au		4 form A + 2 form B, 4 NO + 2 NC contacts	12VDC	800mW		6-1415537-1
SR6A6K18							18VDC			6-1415537-3
SR6A6K24							24VDC			6-1415537-5
SR6B4005	4 form A + 2 form B, 4 NO + 2 NC contacts	AgSnO <sub>2</sub>	5VDC	1200mW	V23050-A1005-A542	1393260-1				
SR6B4006			6VDC		V23050-A1006-A542	1393260-2				
SR6B4012			12VDC		V23050-A1012-A542	1393260-4				
SR6B4018			18VDC		V23050-A1018-A542	1393260-5				
SR6B4021			21VDC		V23050-A1021-A542	1393260-6				
SR6B4024			24VDC		V23050-A1024-A542	1393260-7				
SR6B4040			40VDC		V23050-A1040-A542	1393260-9				
SR6B4048			48VDC		V23050-A1048-A542	1-1393260-0				
SR6B4060			60VDC		V23050-A1060-A542	1-1393260-1				
SR6B4085			85VDC		V23050-A1085-A542	1-1393260-2				
SR6B4110			110VDC		V23050-A1110-A542	1-1393260-3				
SR6B6K12			AgSnO <sub>2</sub> +Au		5 form A + 1 form B, 5 No + 1 NC contacts	12VDC	800mW		7-1415537-6	
SR6B6K15						15VDC			7-1415537-7	
SR6B6K18						18VDC			7-1415537-8	
SR6B6K21						21VDC			7-1415537-9	
SR6B6K24			24VDC				8-1415537-0			
SR6C4012	5 form A + 1 form B, 5 No + 1 NC contacts	AgSnO <sub>2</sub>	12VDC	1200mW	V23050-A1012-A551	1-1415017-1				
SR6C4024			24VDC		V23050-A1024-A551	1415017-1				
SR6C4048			48VDC		V23050-A1048-A551	2-1415019-1				
SR6C4060			60VDC		V23050-A1060-A551	3-1415019-1				
SR6C4110			110VDC		V23050-A1110-A551	5-1415019-1				
SR6C6K24			24VDC			9-1415537-4				
SR6V6K12	4 form A + 2 form B, 4 NO + 2 NC contacts	AgSnO <sub>2</sub> +Au	12VDC	800mW		3-1415542-5				
SR6V6K15			15VDC			2-1415543-2				
SR6V6K18			18VDC			7-1415541-9				
SR6V6K21			21VDC			4-1415542-4				
SR6V6K24			24VDC			5-1415539-2				