



PTC THERMISTORS: TYPE YM120

OVER-CURRENT PROTECTION

DESCRIPTION:

A range of radially-wired PTC disc thermistors with black silicone resin coating.

FEATURES:

- Designed for general purpose over-current, over-voltage and direct over-temperature protection
- Operation up to 265V rms
- Wide range of operating current levels
- Excellent stability
- Fail-safe operation
- Solid state
- High performance barium titanate ceramic
- Suitable for automatic PCB insertion

OPTIONS:

- Non-standard resistances and tolerances
- Resistance matching
- Non-standard wire lengths
- Other wire configurations

PACKAGING:

All types in the YM120 range are available loose-packed, as shown in the drawing. Devices are also available on bandolier (tape & reel): types with diameter a < 14.5mm comply with IEC 286-2.


To identify the packaging required, replace X in the product codes shown in table as follows:

BandolieredR
Loose-packedN


Pack quantities:

Loose-packed500/box
Bandoliered

a < 14.5mm1000/reel (0.5" pitch)
a ≥ 14.5mm500/reel (1" pitch)



DIMENSIONS:



DATA:

Maximum operating voltage265V rms
Switch temperature120°C nominal
Tolerance on R₂₅±20%
Ambient temperature range:
at maximum voltage0 to +55°C
at zero voltage-25 to +155°C
Lead wire materialSolder-coated copper
Body coatingSilicone resin



Component Distributors, Inc. ~ www.cdiweb.com

~ sales@cdiweb.com ~ 1-800-777-7334



PTC THERMISTORS: TYPE YM120

OVER-CURRENT PROTECTION

Code	R ₂₅ Ω	I _{nt} A	I _t A	I _{mo} A	I _r mA	a mm	b mm	Brand code
YM120C15X182	1800	0.016	0.023	0.1	5	4.0	4.5	D
YM120C20X122	1200	0.020	0.028	0.1	6	4.0	4.5	E
YM120C30X601	600	0.028	0.040	0.2	6	4.0	4.5	F
YM120C45X301	300	0.039	0.055	0.2	7	4.0	4.5	G
YM120C60X151	150	0.057	0.080	0.2	7	4.0	4.5	H
YM120C80X101	100	0.070	0.098	0.4	8	4.5	4.5	I
YM120D105X600	60	0.093	0.131	0.6	8	6.0	4.5	J
YM120D125X450	45	0.110	0.155	0.7	9	7.0	4.5	bTh 450
YM120D150X330	33	0.128	0.181	0.9	9	7.5	4.5	bTh 330
YM120D170X250	25	0.161	0.228	1.1	10	8.5	4.5	bTh 250
YM120D200X200	20	0.192	0.265	1.3	11	9.5	4.5	bTh 200
YM120D260X150	15	0.234	0.330	1.7	12	11.5	4.5	bTh 150
YM120D370X100	10	0.314	0.444	2.7	16	14.5	4.5	bTh 100
YM120D480X060	6	0.407	0.575	3.9	25	17.5	4.5	bTh 060

R ₂₅	Resistance at 25°C
I _{nt}	Maximum current without tripping (25°C ambient)
I _t	Minimum trip current (25°C ambient)
I _{mo}	Maximum overload current
I _r	Residual current (25°C ambient)



Component Distributors, Inc. ~ www.cdiweb.com

~ sales@cdiweb.com ~ 1-800-777-7334

Crown Industrial Estate, Priorswood Road
Taunton, Somerset TA2 8QY UK
Tel +44 (0) 1823 335200
Fax +44 (0) 1823 332637

808 US Highway 1
Edison, New Jersey 08817-4695 USA
Tel +1 (732) 287 2870
Fax +1 (732) 287 8847

967 Windfall Road
St. Marys, Pennsylvania 15857-3397 USA
Tel +1 (814) 834 9140
Fax +1 (814) 781 7969