


Phase Control SCR, 70 A



Super-247



1 (K) 2 (A) 3 (G)

DESCRIPTION/FEATURES

The 70TPS..PbF High Voltage Series of silicon controlled rectifiers are specifically designed for high and medium power switching and phase control applications.



RoHS*
COMPLIANT

Typical applications are in input rectification (soft start) or AC-switches or high current crow-bar as well as others phase-control circuits. These products are designed to be used with Vishay HPP input diodes, switches and output rectifiers which are available in identical package outlines.

This product has been designed and qualified for industrial level and lead (Pb)-free ("PbF" suffix).

PRODUCT SUMMARY

V_T at 100 A	< 1.4 V
I_{TSM}	1400 A
V_{RRM}	1200/1600 V

MAJOR RATINGS AND CHARACTERISTICS

PARAMETER	TEST CONDITIONS	VALUES	UNITS
$I_{T(AV)}$	Sinusoidal waveform	70	A
I_{RMS}	Lead current limitation	75	
V_{RRM}/V_{DRM}	Range	1200/1600	V
I_{TSM}		1400	A
V_T	100 A, $T_J = 25^\circ\text{C}$	1.4	V
dV/dt		500	V/ μs
dI/dt		150	A/ μs
T_J		- 40 to 125	$^\circ\text{C}$

VOLTAGE RATINGS

PART NUMBER	V_{RRM}/V_{DRM} , MAXIMUM REPETITIVE PEAK AND OFF-STATE VOLTAGE V	V_{RSM} , MAXIMUM NON-REPETITIVE PEAK REVERSE VOLTAGE V	I_{RRM}/I_{DRM} AT 125 $^\circ\text{C}$ mA
70TPS12PbF	1200	1300	15
70TPS16PbF	1600	1700	

* Pb containing terminations are not RoHS compliant, exemptions may apply

70TPS..PbF High Voltage Series

Vishay High Power Products Phase Control SCR, 70 A



ABSOLUTE MAXIMUM RATINGS						
PARAMETER	SYMBOL	TEST CONDITIONS		VALUES	UNITS	
Maximum average on-state current	I _{T(AV)}	T _C = 82 °C, 180° conduction half sine wave		70	A	
Maximum continuous RMS on-state current as AC switch	I _{T(RMS)}	Lead current limitation		75		
Maximum peak, one-cycle non-repetitive surge current	I _{TSM}	10 ms sine pulse, rated V _{RRM} applied	Initial T _J = T _J maximum	1200		A ² s
		10 ms sine pulse, no voltage reapplied		1400		
Maximum I ² t for fusing	I ² t	10 ms sine pulse, rated V _{RRM} applied		7200	A ² s	
		10 ms sine pulse, no voltage reapplied		10 200		
Maximum I ² √t for fusing	I ² √t	t = 0.1 to 10 ms, no voltage reapplied		102 000	A ² √s	
Low level value of threshold voltage	V _{T(TO)1}	T _J = 125 °C		0.916	V	
High level value of threshold voltage	V _{T(TO)2}			1.21		
Low level value of on-state slope resistance	r _{t1}			4.138	mΩ	
High level value of on-state slope resistance	r _{t2}			3.43		
Maximum peak on-state voltage	V _{TM}	100 A, T _J = 25 °C		1.4	V	
Maximum rate of rise of turned-on current	di/dt	T _J = 25 °C		150	A/μs	
Maximum holding current	I _H	T _J = 25 °C		200	mA	
Maximum latching current	I _L			400		
Maximum reverse and direct leakage current	I _{RRM} /I _{DRM}	T _J = 25 °C	V _R = Rated V _{RRM} /V _{DRM}	1.0		
		T _J = 125 °C		15		
Maximum rate of rise of off-state voltage	dV/dt	T _J = 125 °C			500	

TRIGGERING					
PARAMETER	SYMBOL	TEST CONDITIONS		VALUES	UNITS
Maximum peak gate power	P _{GM}	T = 30 μs		10	W
Maximum average gate power	P _{G(AV)}			2.5	
Maximum peak gate current	I _{GM}			2.5	A
Maximum peak negative gate voltage	- V _{GM}			10	V
Maximum required DC gate voltage to trigger	V _{GT}	T _J = - 40 °C	Anode supply = 6 V resistive load	4.0	
		T _J = 25 °C		1.5	
		T _J = 125 °C		1.1	
Maximum required DC gate current to trigger	I _{GT}	T _J = - 40 °C		270	mA
		T _J = 25 °C		100	
		T _J = 125 °C		80	
Maximum DC gate voltage not to trigger	V _{GD}	T _J = 120 °C, V _{DRM} = Rated value		0.25	V
Maximum DC gate current not to trigger	I _{GD}			6	mA



70TPS..PbF High Voltage Series

Phase Control SCR, 70 A Vishay High Power Products

THERMAL AND MECHANICAL SPECIFICATIONS				
PARAMETER	SYMBOL	TEST CONDITIONS	VALUES	UNITS
Maximum junction temperature range	T _J		- 40 to 125	°C
Maximum storage temperature range	T _{Stg}		- 40 to 150	
Maximum thermal resistance, junction to case	R _{thJC}	DC operation	0.27	°C/W
Maximum thermal resistance, junction to ambient	R _{thJA}		40	
Typical thermal resistance, case to heatsink	R _{thCS}	Mounting surface, smooth and greased	0.2	
Approximate weight			6	g
			0.21	oz.
Mounting torque	minimum		6 (5)	kgf · cm (lbf · in)
	maximum		12 (10)	
Marking device		Case style Super-247	70TPS12	
			70TPS16	

ΔR_{thJ-hs} CONDUCTION PER JUNCTION											
DEVICE	SINE HALF WAVE CONDUCTION					RECTANGULAR WAVE CONDUCTION					UNITS
	180°	120°	90°	60°	30°	180°	120°	90°	60°	30°	
70TPS	0.078	0.092	0.117	0.172	0.302	0.053	0.092	0.125	0.180	0.306	°C/W

Note

- The table above shows the increment of thermal resistance R_{thJ-hs} when devices operate at different conduction angles than DC

70TPS..PbF High Voltage Series

Vishay High Power Products Phase Control SCR, 70 A




Fig. 1 - Current Rating Characteristics




Fig. 4 - On-State Power Loss Characteristics




Fig. 2 - Current Rating Characteristics




Fig. 5 - Maximum Non-Repetitive Surge Current




Fig. 3 - On-State Power Loss Characteristics




Fig. 6 - Maximum Non-Repetitive Surge Current




Fig. 7 - On-State Voltage Drop Characteristics




Fig. 8 - Gate Characteristics




Fig. 9 - Thermal Impedance Z_{thJC} Characteristics

70TPS..PbF High Voltage Series

Vishay High Power Products Phase Control SCR, 70 A



ORDERING INFORMATION TABLE

Device code	70	T	P	S	16	PbF
	1	2	3	4	5	6
	1	-	Current rating (70 = 70 A)			
	2	-	Circuit configuration:			
			T = Thyristor			
	3	-	Package:			
			P = Super-247			
	4	-	Type of silicon:			
			S = Standard recovery rectifier			
	5	-	Voltage code x 100 = V_{RRM}			
						12 = 1200 V 16 = 1600 V
	6	-	• None = Standard production			
			• PbF = Lead (Pb)-free			

LINKS TO RELATED DOCUMENTS	
Dimensions	http://www.vishay.com/doc?95073
Part marking information	http://www.vishay.com/doc?95070



Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.