

Data Sheet | Item Number: 211-812

Nozzles; Length: 12 mm; For the use of 211-811; halogen-free; Cable outer diameter: 1.4 ... 5.0 mm; transparent

<https://www.wago.com/211-812>



Color: transparent

Technical data

| | |
|-----------------|--|
| Suitable | for wire diameter 1.4 ... 5 mm |
| Delivery form | Component |
| Properties | for one 211-811 marker |
| Printing device | Smart Printer (thermal transfer printer) |

Physical data

| | |
|--------|-------|
| Length | 12 mm |
|--------|-------|

Mechanical data

| | |
|---------------|----------------------|
| Mounting type | Sliding on conductor |
|---------------|----------------------|

Material data

| | |
|----------------------|------------------|
| Color | transparent |
| Material | Polyurethane |
| Adhesive information | without adhesive |
| Halogen-free | Yes |
| Weight | 0.2 g |
| Fire load | 0 MJ |

Environmental requirements

| | |
|---------------------------------|----------------|
| Ambient temperature (storage) | +5 ... +40 °C |
| Ambient temperature (operation) | -40 ... +80 °C |
| Relative humidity | 40 ... 80 % |

| Commercial data | |
|-----------------------|--------------------------------|
| Product Group | 2 (Terminal Block Accessories) |
| eCl@ss 10.0 | 27-40-04-01 |
| eCl@ss 9.0 | 27-40-04-01 |
| ETIM 9.0 | EC001530 |
| ETIM 8.0 | EC001530 |
| PU (SPU) | 500 pcs |
| Packaging type | Box |
| Country of origin | IT |
| GTIN | 4050821674986 |
| Customs tariff number | 39269097900 |

| Environmental Product Compliance | |
|----------------------------------|-------------------------|
| RoHS Compliance Status | Compliant, No Exemption |

Downloads

Environmental Product Compliance

| Compliance Search | |
|--|---|
| Environmental Product Compliance 211-812 | ↓ |

1 Compatible Products

1.1 Required Accessories

1.1.1 Marking

1.1.1.1 Marker



Item No.: 211-811
 Marker; for Smart Printer; for use in nozzles; Length: 12 mm; white


Installation Notes

Application



Slide the marker into the marking sleeve receptacle. Replacing the marker is also possible after the conductor has been terminated.

Application



Compress the sleeve and slide it onto the conductor to be marked.