## Materials:


Insulating housing: moulded plastic type 150, creepage resistant
Terminal compartment and cover mounting

screws - brass with nickel plating Terminal screws - galvanised and chrome plated steel Wire protection - phosphor bronze

while protection - phosphor bronze

T = (pole number -1) x 12

 $G = \ddot{T} + 30$ 



with WP up to 2.5 mm<sup>2</sup>/finely stranded

EN 60998-1/-2-1 5
Rated cross section, single core 4
Rated cross section, finely stranded 2
Approvals 3

500 V; 32 A; 4 mm<sup>2</sup> 2.5 mm<sup>2</sup>

	Pole	G	Туре	Part No.	Box Oty	
with screw terminals and	2	42	KBD 1/ 2 KR	28.121.0240.0	50	
wire protection	3	54	KBD 1/3 KR	28.121.0340.0	40	
·	4	66	KBD 1/ 4 KR	28.121.0440.0	30	
	5	78	KBD 1/5 KR	28.121.0540.0	25	
	6	90	KBD 1/ 6 KR	28.121.0640.0	20	
	7	102	KBD 1/ 7 KR	28.121.0740.0	20	
		102	KDD I/ / KII	20.121.0740.0		
	8	114	KBD 1/8 KR	28.121.0840.0	20	
	10	138	KBD 1/10 KR	28.121.1040.0	15	
	12	162	KBD 1/12 KR	28.121.1240.0	15	